

TECHNICAL DATA

CLASSIFICATION			
Reaction to Fire	EN 13 501-1	class	B-s2,d0
Thermal Resistance(TR)	EN 12667	[m2K/W]	0,010
Dimensional Stability	EN ISO 23999	[%]	≤0,05
Residual Indentation (RI)	EN ISO 24343	[mm]	0,01
Formaldehyde Content	EN 12149	-	PASS
Heavy Metals Content	EN 12149	-	PASS
Vinyl Chloride Monomer Content	EN 12149	-	PASS
Sound Absorption	EN ISO 354	-	NPD
PERFORMANCE			
Scratch Resistance	EN ISO 1518	[N]	24
Stain and chemical resistance	EN ISO 26987	[-]	Index 0
Abrasion Resistance	EN ISO 13329	[cycles]	500
ENVIRONMENT	100% recyclable		
PANELS			
Total Thickness	EN ISO 24346	[mm]	3.7
Wearlayer Thickness		[mm]	0.1
Unit package: Carton	2 panels	2.88m²	
Weight	EN ISO 23997	[g/m²]	7700
Dimensions	EN ISO 24341	[mm]	600x2400
TILES			
Total Thickness	EN ISO 24346	[mm]	3.7
Wearlayer Thickness		[mm]	0.1
Unit package: Carton	4 panels	2.88m²	
Weight	EN ISO 23997	[g/m2]	7700
Dimensions	EN ISO 24341	[mm]	600x1200
CUSTOMIZABLE SIZE			
400mmx800mm / 475mmx900mm(A length ranging from 900mm to 2600mm)			
600mmx1200mm(A length ranging from 1200mm to 2600mm)			
600mmx2440mm(A length ranging from 2440mm to 2600mm)			
1200mmx2440.mm(A length ranging from 2440mm to 2600mm)			

